

Product Datasheet

Cure It

Product description

Cure It is a fully-formulated, wet-laid, GRP waterproofing system.

Material features

- Materials are specially formulated for roofing applications
- 20 year guarantee on materials
- Fast 'wet-out'
- Low styrene emission
- High flexibility
- Adjusted for seasonal variations in temperature
- Good inter-laminar adhesion
- Includes technical support
- Full training and on-site support available
- Easy to use (provided in kit format with instructional DVD and manual)
- Supplied pre-pigmented mid-grey (BS 00 A 09)
- Any BS4800 colour available
- Fire retardant to BS476-3 Ext.F.AB (no restrictions on usage) F.AA rating is available with the coated non-slip finish.

Longevity

The Cure It roofing system materials (Roofing Resin, Roofing Topcoat, Roofing Edge Trims, Roofing Catalyst, Chopped Strand Mat) will remain within the specification of the Cure It Material Safety Data Sheet when stored correctly and will form a structural waterproof membrane that will remain watertight for a period of 20 years from the date of manufacture when installed as specified in the conditions set out in the Cure It guarantee.

Properties in relation to fire

A flat roofing system comprising of a Cure It GRP laminate with Cure It topcoat when tested to BS 476-3 : 2004 was designated EXT.F.AB (no limitations on use.)

Resistance to wind uplift

The Cure It GRP roofing system is fully-bonded to the roof substrate. The system will be resistant to any wind uplift that could reasonably be expected during the product's lifespan.

Areas of usage

The Cure It waterproofing system can be used for waterproofing applications of almost any size or complexity.

Warm roof specification

The Cure It system can be specified to comply with current part 'L' regulations.

Resistance to foot traffic

In standard 450g/m² specification the Glass Guard system will be resistant to any level of foot traffic that it could reasonably be subjected to during its lifespan. 600g/m² specification is available for applications subject to heavy foot traffic such as walkways/balconies.

Finish options

The Cure It waterproofing system is supplied to BS4800 00 A 09 mid grey. There are two non-slip options available: coloured non-slip (granulated non-slip slate coating applied at 1000g/m²) and coated non-slip (granulated non-slip slate coating applied at 1500g/m²).

Product Range

Cure It Roofing Kit 10m²

- Includes: -15kg Cure It roofing resin
- 5kg Cure It roofing topcoat (BS4800 00 A 09 Mid Grey)
- 15m X 95cm 450g Chopped Strand Mat
- 1 300ml tube PU adhesive
- 2 X 400ml catalyst
- 16m X 75mm 450g Chopped Strand Mat bandage
- Installation guide
- Installation DVD

Cure It CSM mat kit (enough for 10m²)

Cure It Roofing Resin 20kg

Cure It Roofing Topcoat 20kg Clear

Cure It Roofing Topcoat 20kg (BS4800 00 A 09 Mid Grey)