


Therma^oroof TR20


INSULATION BENEATH PARTIALLY BONDED BUILT-UP FELT



- High performance rigid urethane insulation – thermal conductivity 0.026–0.028 W/m-K
- Fully compatible with most bitumen based waterproofing systems
- Industry standard for built-up felt waterproofing systems
- Available in a tapered version
- Resistant to the passage of water vapour
- Easy to handle and install
- Ideal for newbuild and refurbishment
- Non-deleterious material
- CFC/HCFC-free with zero Ozone Depletion Potential (ODP)



Typical Design Detail



Specification Clause

Kingspan **Therma**roof TR20 should be described in specifications as:-

The roof insulation shall be **Kingspan Therma**roof TR20 _____mm thick comprising a CFC/HCFC-free rigid urethane insulation core with bitumen impregnated glass tissue facings on both sides manufactured to the highest standards in accordance with both the requirements of draft BS 4841-3 and quality control systems approved to BS EN ISO 9001: 2000 by Kingspan Insulation Limited and shall be applied in accordance with the instructions issued by them.

Details also available in NBS PLUS.
NBS users should refer to clause(s):
J41 420, J41 430
(Standard and Intermediate)
J41 10 (Minor Works).



Design Considerations

Sustainability

In the past, erroneously, the relative environmental sustainability of insulation materials has been compared on the basis of embodied energy and ozone depletion potential. It is now recognised that a much wider basket of embodied environmental impacts (including those caused by their embodied energy), rather than embodied energy alone, is the only credible tool of comparison. Time has also annulled ozone depletion potential as an issue as all insulation materials are now banned from using CFC and HCFC blowing agents by law.

For buildings designed to today's Building Regulations energy use standards it is now also known that the embodied environmental impacts of all of the materials and labour used to create a building are insignificant in comparison with the lifetime operational environmental impacts of that building and so are of very limited importance. Since it is operational energy use that creates the vast majority of operational environmental impact, saving energy by specifying the lowest U-values possible is the most environmentally sustainable action to take.

However, one of the most neglected facts about environmentally sustainable buildings is that the longevity of their standards of operational energy use, and therefore the longevity their operational environmental impacts, is critical. The performance of some insulants, such as mineral fibre, can deteriorate rapidly if exposed to water penetration, air movement or compression. This may increase operational energy use and hence compromise the environmental sustainability of the finished building to an alarming degree. Other insulation materials, such as rigid phenolic or rigid urethane, are not vulnerable to any of these problems.

In summary, designers should:

- (a) specify the lowest possible U-value regardless of insulation type;
- (b) design out the risk of their chosen insulant not performing as specified; and (c) if the latter is not possible, choose an insulant that is at low risk of failure e.g. a cellular plastic insulation material.

However, manufacturers should not rest on their laurels, it is a matter of social responsibility to be open and honest about the environmental impact of the manufacture of a product, and a full Life Cycle Analysis (LCA) based on a much wider basket of environmental impacts, rather than embodied energy alone, is recognised as the preferred tool to achieve this.

Kingspan Insulation was the first insulation manufacturer to complete and openly publish an independently certified Ecoprofile (a type of LCA) on one of its product ranges. The Ecoprofile was carried out on the Therma zero ODP range of rigid urethane insulation products by the Building Research Establishment (BRE). The product range comfortably achieves a BRE Green Guide A rating.



But there is far more to sustainability than whether or not a product, process or company affects the environment in a positive or a negative way. A company can and should demonstrate its financial viability and social responsibility, as well as ensure that its materials and methods do not add unduly to the burden placed on the planet.

Kingspan Insulation has now put the manufacture of its products at its Pembridge facility in Herefordshire through a rigorous independent appraisal of its economic, social, environmental and natural resource impacts using Arup's SPeAR® tool.

The results show a well balanced performance in terms of sustainability, and that Kingspan Insulation is already meeting legislation or best practice in most areas, even moving beyond best practice in some. Kingspan Insulation is the first and only construction material manufacturer to have taken this bold move and openly publish the results.

Wind Loading

Wind loading should be assessed in accordance with BS 6399-2: 1997 (Loading for buildings. Code of practice for wind loads).

Roof Waterproofing

*Kingspan Therma*roof TR20 is suitable for use with most bitumen based waterproofing systems including high performance types which incorporate and are compatible with a Type 3G perforated base layer to BS 747: 2000 (Reinforced bitumen sheets for roofing. Specification). The 3G felt layer is laid dry and loose, mineral face down with a fully bonded perimeter zone. The roof waterproofing should be applied as soon as possible after the laying of the boards. The built-up roof specification should be laid where applicable in accordance with BS 8217: 2005 (Reinforced bitumen membranes for roofing. Code of practice). Certain approved single ply membranes are also compatible.

Please Note: *Kingspan Therma*roof TR20 is unsuitable for use with mastic asphalt waterproofing.

Falls

The fall on a flat roof should be smooth and steep enough to prevent the formation of rainwater pools. To ensure adequate drainage, BS 6229: 2003 (Flat roofs with continuously supported coverings. Code of practice), recommends uniform gradients of not less than 1 in 80. However, because of building settlement, it can be advisable to 'design in' even greater falls. These can be provided by the use of Kingspan Insulation's Tapered Roofing Systems.

Tapered Roofing

*Kingspan Therma*roof TR20 is also available in a tapered version (*Kingspan Therma*aper® TT40), comprising a high performance CFC/HCFC-free rigid urethane core autohesively bonded to bitumen impregnated glass tissue facings during manufacture. Further details of the *Kingspan Therma*aper® range and a complete design service are available from the Kingspan Insulation Tapered Roofing Department who should be consulted as early as possible in the process of roof design in order that they may offer the benefit of their considerable experience to the design team.

Water Vapour Control

The need for a separate vapour control layer with *Kingspan Therma*roof TR20 in a warm roof construction should be assessed in accordance with BS 5250: 2002 (Code of practice for control of condensation in buildings) and as defined in BS 6229: 2003. A minimum vapour control layer should consist of a coated roofing felt complying with BS 747: 2000 Type 3B, or any appropriate metal-cored vapour control layer. Allowance should be made for the adequate bonding of the vapour control layer to the deck so as to provide a suitable surface for *Kingspan Therma*roof TR20 to be laid upon, and sufficient resistance to wind up-lift (see 'Wind Loading').

Roof Loading

Depending on the chosen waterproofing system, *Kingspan Therma*roof TR20 is suitable for use on access roof decks subject to limited foot traffic. Where continuous or excessive loadings are liable to occur it is recommended that the roof surface is protected by promenade tiles. The roof should be adequately protected when building works are being carried out on or over the roof surface. This is best achieved by close boarding. The completed roof must not be used for storage of heavy building components such as bricks or air conditioning equipment.

Spanning on Metal Decks

The designer's attention is drawn to the requirement that insulation boards comply with the minimum thicknesses shown in the table below, when used over metal decks with trough openings as shown.

Trough Opening (mm)	Minimum Insulant Thickness (mm)
≤ 75	25
76–100	30
101–125	35
126–150	40
151–175	45
176–200	50

Typical U-values

The following examples have been calculated using the combined method for compliance with Building Regulations/Standards revised after the year 2002. These examples are based on the use of *Kingspan Therma^{roof} TR20* waterproofed using 3 layers of built-up felt with the surface covered with mineral chippings. The board is laid over a bitumen based vapour control layer, which is fully bonded, to the type of deck stated for each application. The suspended ceiling, where shown, is taken to be 12.5 mm plasterboard with a cavity between it and the underside of the deck. If your construction is any different, please contact the Kingspan Insulation Technical Services Department (see rear cover).

Combined Method – U-values were calculated using the method which has been adopted to bring National standards in line with the European Standard calculation method, BS/I.S. EN ISO 6946: 1997 (Building components and building elements. Thermal resistance and thermal transmittance. Calculation method).

NB when calculating U-values using the combined method as detailed in BS/I.S. EN ISO 6946: 1997, the type of mechanical fixing used may change the thickness of insulation required. The effect of fixings have been ignored for the purposes of these calculations. Please contact the Kingspan Insulation Technical Services Department (see rear cover) for project calculations.

NB for the purposes of these calculations the standard of workmanship has been assumed good and therefore the correction factor for air gaps has been ignored.

The figures below are for guidance only. A detailed U-value calculation together with condensation risk analysis should be completed for each individual project. Please call the Kingspan Insulation Technical Services Department for assistance (see rear cover).

Metal Deck with no Ceiling

Insulant Thickness (mm)	U-value (W/m ² ·K)
55	0.44
60	0.41
70	0.36
75	0.33
80	0.31
85	0.29
90	0.27
95	0.26
100	0.25
105	0.24
110	0.23
115	0.22
120	0.20
125	0.20
130	0.19
135	0.18
140	0.18
145	0.17
150	0.16

Dense Concrete Deck with Suspended Ceiling

Insulant Thickness (mm)	U-value (W/m ² ·K)
45	0.46
50	0.43
60	0.37
65	0.35
70	0.33
75	0.31
80	0.28
85	0.27
90	0.26
95	0.25
100	0.23
105	0.23
110	0.22
115	0.21
120	0.19
125	0.19
130	0.18
135	0.17
140	0.17
145	0.16

Timber Deck with Plasterboard Ceiling

Insulant Thickness (mm)	U-value (W/m ² ·K)
45	0.46
50	0.42
60	0.37
65	0.34
70	0.32
75	0.31
80	0.28
85	0.27
90	0.26
95	0.24
100	0.23
105	0.22
110	0.21
115	0.21
120	0.19
125	0.19
130	0.18
135	0.17
140	0.17
145	0.16

Sitework

Vapour Control Layer

Metal decks and concrete decks should be primed in accordance with the appropriate manufacturers instructions prior to the application of the hot bitumen or suitable alternative proprietary adhesive system used to bond the vapour control layer to the deck.

The specified vapour control layer should be continued 25 mm past the insulation abutting the parapet and sealed.

Fixing over Metal Decks

On metal decks, *Kingspan Therma*roof TR20 should be laid over the vapour control layer. The boards are normally secured using mechanical fixings and washers. The *Kingspan*

*Therma*roof TR20 boards should be laid break-bonded with their long edges at right angles to the trough openings, or alternatively, diagonally across the corrugation line. Whichever system is chosen, care must be taken to ensure that all joints are supported by the deck. The joints should be lightly butted. Alternatively the boards can be either laid into hot bitumen (max. temperature 240°C) mopped or poured over the vapour control layer or with the use of suitable alternative proprietary adhesive systems. However, advice should be sought from the appropriate manufacturer of the adhesive system for their recommendations on the correct procedure for application rates and application temperatures.

Fixing over Concrete Decks

Concrete decks should be clean, dry, without large projections, steps or gaps, and should be graded to allow correct falls to all rainwater outlets. To ensure an adequate bond between the vapour control layer and the concrete deck, the concrete or screeded surface should be suitably primed, in accordance with the specified manufacturer's instructions. The vapour control layer should be fully bonded to the deck and similarly the *Kingspan Therma*roof TR20 to the vapour control layer by laying into hot bitumen mopped or poured over the vapour control layer or with the use of suitable alternative proprietary adhesive systems. However, advice should be sought from the appropriate manufacturer of the adhesive system for their recommendations on the correct procedure for application rates and application temperatures. Alternatively the boards can be secured using mechanical fixing systems (see Figure 1). The boards should be laid break-bonded with all joints lightly butted.

Fixing over Plywood Decks

*Kingspan Therma*roof TR20 should be fully bedded in hot bitumen or with the use of suitable alternative proprietary adhesive systems. However, advice should be sought from the appropriate manufacturer of the adhesive system for their recommendations on the correct procedure for application rates and application temperatures over a continuous vapour control layer, which has been nailed or fully bonded to the deck, with laps at the side and end sealed with either the use of hot bitumen or one the alternative proprietary adhesive systems as detailed previously. Alternatively the boards can be secured using mechanical fixing systems (see Figure 1). The joints should be break-bonded and the boards laid at right angles to the edge of the roof or diagonally across the roof. All joints should be lightly butted.

Fixing over Tongue and Groove Decks

On timber tongue and groove decks, the vapour control layer should be nailed. The *Kingspan Therma*roof TR20 is then applied as described under plywood decks. During the laying of *Kingspan Therma*roof TR20 the nail heads will become sealed with either the use of hot bitumen or one of the alternative proprietary adhesive systems as detailed previously for plywood decks to the vapour control layer by the subsequent bonding of the roofboard.

Fixing over Woodwool Decks

On woodwool slab decks, *Kingspan Therma*roof TR20 should be fully bedded in hot bitumen or with the use of suitable alternative proprietary adhesive systems. However, advice should be sought from the appropriate manufacturer of the adhesive system for their recommendations on the correct procedure for application rates and application temperatures over a continuous vapour control layer. Boards should be laid with their long edges at right angles to the slabs, or preferably diagonally across the roof. Alternatively boards can be secured using specialist mechanical fixing systems (see Figure 1). Board joints should not coincide with those of the slabs. The roof boards should be laid break-bonded, with all joints lightly butted.

Mechanical Fixings

The number of mechanical fixings required to fix *Kingspan Therma*roof TR20 will vary with the geographical location of the building, the topographical data, and the height and width of the roof concerned.

Each fixing should incorporate a square or circular plate washer (50 mm x 50 mm or 50 mm diameter).

A minimum 4 No. fixings should be placed within the individual board area and be sited > 50 mm and < 150 mm from the edges and corners of the board giving a minimum fixing rate of 5.55 fixings per square metre: (1.2 x 0.6 m boards).

The requirement for additional fixings should be assessed in accordance with BS 6399-2: 1997 (see Figure 1).




Figure 1 Typical Mechanical Fixing Pattern

Therma^{roof} TR20

Perimeter Mechanical Fixings

Where perimeter mechanical fixings are specified, the minimum number and distribution should be as stated for full mechanical fixing. The extent of the perimeter mechanical fixing will depend on the design and location of the roof concerned.

The fixings should cover a distance of not less than two metres from the edge of the roof. The area to be mechanically fixed should extend around the complete perimeter of the roof.

Reflective Coatings

Bitumen based built up waterproofing systems laid over *Kingspan Therma^{roof} TR20* should always incorporate a solar reflective layer such as chippings or specialist coatings.

Daily Working Practice

At the completion of each day's work, or whenever work is interrupted, a night joint must be made in order to prevent water penetration of the roof construction.

Cutting

Cutting should be carried out using a fine toothed saw or by scoring with a sharp knife and snapping the board over a straight edge and cutting the facing on the other side. Ensure accurate trimming to achieve close butting joints and continuity of insulation.

Availability

Kingspan Therma^{roof} TR20 is available through specialist insulation distributors and selected roofing merchants throughout the UK, Ireland and Europe.

Packaging

The boards are supplied in labelled packs shrinkwrapped in polythene.

Storage

The packaging of *Kingspan Therma^{roof} TR20* should not be considered adequate for long term outside protection. Ideally boards should be stored inside a building. If outside storage cannot be avoided the boards should be stacked clear of the ground and covered with a polythene sheet or weatherproof tarpaulin. Boards that have been allowed to get wet should not be used.

Health and Safety

Kingspan Insulation products are chemically inert and safe to use. A leaflet on this topic which satisfies the requirements set out in the Control of Substances Hazardous to Health Regulations 1988 (COSHH) is available from the Kingspan Insulation Marketing Department (see rear cover).

Warning – do not stand on or otherwise support your weight on this board unless it is fully supported by a load-bearing surface.

Product Description

The Facings

Kingspan Therma^{roof} TR20 is faced on both sides with bitumen impregnated glass tissue autohesively bonded to the insulation core during manufacture.

The Core

The core of *Kingspan Therma^{roof} TR20* is a high performance CFC/HCFC-free rigid urethane insulant of typical density 32 kg/m³.

CFC/HCFC-free

Kingspan Therma^{roof} TR20 is manufactured without the use of CFCs/HCFCs and has zero Ozone Depletion Potential (ODP).



Product Data

Standards and Approvals

Kingspan Therma^{roof} TR20 is manufactured to the highest standards in accordance with requirements of draft BS 4841-3 (Rigid Polyurethane (PUR) and Polyisocyanurate (PIR) products for building and end-use applications. Specification for laminated insulation boards (roofboards) with auto-adhesively bonded facings for use as roofboard thermal insulation for built-up roofs under bituminised roofing membranes).

Kingspan Therma^{roof} TR20 is manufactured to the highest standards under a quality control system approved to BS EN ISO 9001: 2000 (Quality management systems). Requirements). Its use is covered by BBA Certificate 97/3364.



Manufactured to BS EN ISO 9001: 2000
Certificate No. 388



Standard Dimensions

Kingspan Therma^{roof} TR20 is available in the following standard sizes and thicknesses:

Nominal Dimension	Availability
Length (m)	1.2
Width (m)	0.6
Insulant Thickness (mm)	Refer to local distributor or Kingspan Insulation price list for current stock and non-stock sizes.

Insulation Compressive Strength

Typically exceeds 150 kPa at 10% compression and 125 kPa at 5% compression when tested to BS EN 826: 1996 (Thermal insulating products for building applications. Determination of compression behaviour).

Water Vapour Resistance

The boards achieve a resistance greater than 15 MN·s/g, when tested in accordance with BS 4370-2: 1993 (Methods of test for rigid cellular materials. Methods 7 to 9). *Kingspan Therma*roof TR20 should always be installed over a separate felt vapour control layer (see 'Water Vapour Control' page 3).

Durability

If correctly applied, *Kingspan Therma*roof TR20 has an indefinite life. Its durability depends on the supporting structure, waterproofing and the conditions of its use.

Resistance to Solvents, Fungi & Rodents

The insulation core is resistant to short-term contact with petrol and with most dilute acids, alkalis and mineral oils. However, it is recommended that any spills be cleaned off fully before the boards are installed. Ensure that safe methods of cleaning are used, as recommended by the suppliers of the spilled liquid. The insulation core is not resistant to some solvent-based adhesive systems, particularly those containing methyl ethyl ketone. Adhesives containing such solvents should not be used in association with this product. Damaged boards or boards that have been in contact with harsh solvents or acids should not be used.

The insulation core and facings used in the manufacture of *Kingspan Therma*roof TR20 resist attack by mould and microbial growth and do not provide any food value to vermin.

Fire Performance

Flat roofs insulated with *Kingspan Therma*roof TR20 when subjected to British Standard fire tests achieve the following typical results when waterproofed with 3 layer built-up felt and a loading coat of 10 mm chippings. For specifications without the chippings please consult the manufacturer of the mineral surfaced cap sheet for their fire classification details.

Test	Result
BS 476-3: 1958 (External fire exposure roof test)	FAA rating

Further details on the fire performance of Kingspan Insulation products may be obtained from the Kingspan Insulation Technical Services Department (see rear cover).

Thermal Properties

The λ -values and R-values quoted are in accordance with the Harmonised European Standard BS EN 13165: 2001 (Thermal insulation products for buildings – Factory made rigid polyurethane foam (PUR) products – Specification) using so called 90/90 principles. Comparison with alternative products may not be appropriate unless the same procedures have been followed.

Thermal Conductivity

The boards achieve a thermal conductivity (λ -value) of 0.028 W/m·K (insulant thickness < 80 mm), 0.027 W/m·K (insulant thickness 80–119 mm) and 0.026 W/m·K (insulant thickness \geq 120 mm).

Thermal Resistances

Thermal resistance (R-value) varies with thickness and is calculated by dividing the thickness of the board (expressed in metres) by its thermal conductivity.

Insulant Thickness (mm)	Thermal Resistance (m ² ·K/W)
45	1.60
50	1.75
55	1.95
60	2.10
65	2.30
70	2.50
75	2.65
80	2.95
85	3.10
90	3.30
95	3.50
100	3.70
105	3.85
110	4.05
115	4.25
120	4.60
125	4.80
130	5.00
135	5.15
140	5.35
145	5.55
150	5.75

Refer to local distributor or Kingspan Insulation price list for current stock and non-stock sizes.

Contact Details

Customer Service

For quotations, order placement and details of despatches please contact the Kingspan Insulation Customer Services Department on the numbers below:

UK	– Telephone:	+44 (0) 870 850 8555
	– Fax:	+44 (0) 870 850 8666
	– email:	commercial.uk@insulation.kingspan.com
Ireland	– Telephone:	+353 (0) 42 97 95000
	– Fax:	+353 (0) 42 97 46129
	– email:	commercial.ie@insulation.kingspan.com

Literature & Samples

Kingspan Insulation produce a comprehensive range of technical literature for specifiers, contractors, stockists and end users. The literature contains clear 'user friendly' advice on typical design; design considerations; thermal properties; sitework and product data.

Available as a complete Design Manual or as individual product brochures, Kingspan Insulation technical literature is an essential specification tool. For copies please contact the Kingspan Insulation Marketing Department on the numbers below:

UK	– Telephone:	+44 (0) 870 733 8333
	– Fax:	+44 (0) 1544 387 299
	– email:	literature.uk@insulation.kingspan.com
Ireland	– Telephone:	+353 (0) 42 97 95038
	– Fax:	+353 (0) 42 97 46129
	– email:	literature.ie@insulation.kingspan.com

Tapered Roofing

For technical guidance, quotations, order placement and details of despatches please contact the Kingspan Insulation Tapered Roofing Department on the numbers below:

UK	– Telephone:	+44 (0) 870 761 7770
	– Fax:	+44 (0) 1544 387 289
	– email:	tapered.uk@insulation.kingspan.com
Ireland	– Telephone:	+353 (0) 42 97 95032
	– Fax:	+353 (0) 42 97 95669
	– email:	tapered.ie@insulation.kingspan.com

Technical Advice/Design

Kingspan Insulation Ltd support all of their products with a comprehensive Technical Advisory Service for specifiers, stockists and contractors.

This includes a computer-aided service designed to give fast, accurate technical advice. Simply phone the Kingspan Insulation **TECHLINE** with your project specification. Calculations can be carried out to provide U-values, condensation/dew point risk, required insulation thicknesses etc... Thereafter any number of permutations can be provided to help you achieve your desired targets.

The Kingspan Insulation Technical Services Department can also give general application advice and advice on design detailing and fixing etc... Site surveys are also undertaken as appropriate.

Please contact the Kingspan Insulation Building Fabric Insulation Technical Services Department on the **TECHLINE** numbers below:

UK	– Telephone:	+44 (0) 870 850 8333
	– Fax:	+44 (0) 1544 387 278
	– email:	techline.uk@insulation.kingspan.com
Ireland	– Telephone:	+353 (0) 42 97 95032
	– Fax:	+353 (0) 42 97 95669
	– email:	techline.ie@insulation.kingspan.com

General Enquiries

For all other enquiries contact Kingspan Insulation on the numbers below:

UK	– Telephone:	+44 (0) 870 850 8555
	– Fax:	+44 (0) 870 850 8666
	– email:	info.uk@insulation.kingspan.com
Ireland	– Telephone:	+353 (0) 42 97 95000
	– Fax:	+353 (0) 42 97 46129
	– email:	info.ie@insulation.kingspan.com

Kingspan Insulation reserve the right to amend product specifications without prior notice. Product thicknesses shown in this document should not be taken as being available ex-stock and reference should be made to the current Kingspan Insulation price-list or advice sought from Kingspan Insulation Sales Department. The information, technical details and fixing instructions etc. included in this literature are given in good faith and apply to uses described. Recommendations for use should be verified as to the suitability and compliance with actual requirements, specifications and any applicable laws and regulations. For other applications or conditions of use, Kingspan Insulation offers a Technical Advisory Service (see left) whose advice should be sought for uses of Kingspan Insulation products that are not specifically described herein. Please check that your copy of the literature is current by contacting the Kingspan Insulation Marketing Department (see above).



Kingspan Insulation Ltd

Pembridge, Leominster, Herefordshire HR6 9LA, UK
Castleblayney, County Monaghan, Ireland

www.insulation.kingspan.com